



Zip Wall Fountain[®]

Wall-mounted chillers

Filtered drinking water



Features

Recessed chiller ideal for providing chilled filtered water where space is at a premium

Perfect for installing in busy corridors

Equipped with carafe filler and bubbler

Lockable front panels

Stainless steel case construction

WRAS approved and CE endorsed

01.01.10



	Product code	Dimensions (mm) H x W x D	Initial draw off (glasses*)	Recovery (glasses per hour)	Compressor (hp)
Zip Wall Fountain® 1.8 litre	CH104	1670 x 635 x 303	8	140	1/4

- Wall-recessed chilled water dispenser
- Delivers 140 glasses per hour of chilled filtered water within the operating range of 5°C to 10°C
- Equipped with a carafe filler and a bubbler.
- Lockable front access panels
- Compressor rated at 1/4 hp.
- Equipped with sub-micron filtration
- Brushed finished stainless steel water bowl and outer case.
- 15mm BSP water connections

Storage capacity

Nominal 1.8 litres.

Output capacity

Rated at 140 glasses per hour at <10°C.

Rating

0.3 kW.

Refrigerant type

Non-toxic R134A.

Chiller type

Fan cooled condensor with a compressor rated at 1/4 hp.

Configuration

Equipped with carafe filler and bubbler.

Outer case

Brushed finish stainless steel case with lockable front access panel.

Filtration type

Submicron fully encapsulated double action carbon filter.

Approvals

WRAS approved and CE endorsed.

Warranty

One-year on site parts and labour. For full details of the Zip Warranty Scheme visit: www.zipheaters.co.uk/warranty.

Installation

Location

The chiller should be recessed into a wall where it is easy for users to access.

Water, drainage and power should all be available nearby.

Plumbing

Water connections 15mm BSP.

Should be installed only by a qualified plumber.

Electrical

To be wired to a double pole switched fused spur with a minimum break capacity of 13 amps.

Installation must comply with current IEE regulations.

Dimensions

