



HydroTap Domestic

A range of instant boiling chilled and filtered water systems specifically designed for use in the home

All products in the range feature the iconic cool-touch taphead, incorporating a unique safety lock. The tap can be mounted either over a sink, or, using the optional tap font and drain, on any worktop.

The tap has a high quality chrome plated, die cast body with push and pull levers for electronically controlled water delivery. Integral LED light indicate the status of the boiling / chilled water and filter change.



The boiling chilled and boiling only options are available with a brushed stainless steel finish option and oversize levers for less dexterous users are available on request.



DOMBC1 – Boiling / Chilled Compact



DOMBA1 – Boiling / Ambient



DOMHB1 – Boiling only



DOMBC2 – Boiling / Chilled Split



HydroTap Domestic

Specification	DOMHB1	DOMBA1	DOMBC1	DOMBC2
Dimensions (Width x Depth x Height)	188 x 320 x 334	280 x 323 x 337	385 x 380 x 348	280 x 323 x 337 (B) 353 x 253 x 377 (C)
Power rating (kW)	1.5	1.5	1.7	1.7
Boiling tank capacity (Litres)	2.2	3.0	2.2	3.0
Chilled tank capacity (Litres)	N/A	N/A	1.8	
Boiling tank material	Stainless Steel	Stainless Steel	Copper	Stainless Steel
Chilled tank material	N/A	N/A	Copper	Stainless Steel
Delivery method - boiling water	Pumped	Pumped	Pumped	Pumped
Delivery method – chilled water	N/A	N/A	Push through	Push through
Cups per hour - boiling	60	60	60	60
Glasses per hour – chilled	N/A	N/A	85	85
Set temperature – boiling (°C)	98	98	98	98
Set temperature – chilled (°C)	N/A	N/A	5-10	5-10
Flow – boiling (Litres/min)	3.8	3.8	3.8	3.8
Flow – chilled (Litres/min)	N/A	N/A	3.2 @3.5 bar	3.2 @3.5bar
Sleep mode	No	Yes	Yes	Yes
Timer	No	Yes	Yes	Yes
Boiling safety lock	Yes	Yes	Yes	Yes
Adjustable dispense time	No	Yes	Yes	Yes
Integral submicron filtration	No	Yes	Yes	Yes